

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:	)	
	)	
<b>Hans Schwade, et al.</b>	)	
	)	Art Unit: 1744
Serial No.: 10/612,195	)	
	)	Examiner: David A. Redding
Filed: July 2, 2003	)	
	)	
For: Integral Packing Housing and	)	
Packing Material Unit	)	

---

AMENDMENT

---

Commissioner for Patents  
Mail Stop Non-Fee Amendment  
P.O. Box 1450  
Alexandria, VA 22313-1450

November 1, 2007

**Customer Number 35725**

Sir:

In response to the Official Action mailed October 4, 2007, please cancel Claim 29 and enter the following amendments as shown to place the application in condition for allowance.

Respectfully submitted,

**/Michael J. Mehrman/**  
By: Michael J. Mehrman  
Reg. No. 40,086

Mehrman Law Office, P.C.  
5605 Glenridge Drive  
Suite 795  
Atlanta, GA 30342  
404 497 7400  
404 497 7405  
mike@mehrmanlaw.com

### Claims

1. (previously presented) An integral and removable packing unit, comprising:  
a housing for removably holding a sacrificial packing material configured to form a steam seal between a sootblower steam tube and lance spindle when the packing unit is installed in an operative position in association with the steam tube and the spindle and the packing material is loaded by applying compression to the packing material; and

wherein the housing and packing material comprise an integral unit constructed so as to be installed to and removed from the steam tube and spindle with the packing material held intact within the housing.

2. (previously presented) The packing unit of claim 1, further comprising a compression unit for compressing the packing material to tighten the seal between steam tube and lance spindle when the packing unit is installed in the operative position.

3. (previously presented) The packing unit of claim 1, further comprising a detent mechanism for unloading the packing material to facilitate installing the packing unit on, and removing the packing unit from, the operative position.

4. (currently amended) The packing unit of claim 3, ~~wherein the~~ further comprising a compression unit ~~comprises~~ comprising one or more coil springs located between first and second compression plates.

5. (previously presented) The packing unit of claim 4, wherein:  
the packing unit defines a cylindrical opening for receiving the steam tube, and  
the packing material comprises a series of equally-sized, concentric, sacrificial packing rings having an inner dimension approximately equal to an outer dimension of the steam tube and an outer dimension approximately equal to an inner dimension of the housing.

6. (previously presented) The packing unit of claim 5, wherein the compression unit comprises a plurality of coil springs located around the cylindrical opening.

7. (previously presented) The packing unit of claim 6, wherein the detent mechanism comprises one or more set screws that threadably engage at least one of the compression plates to compress the coil springs and thereby unload the packing material.

8. (previously presented) The packing unit of claim 1, further comprising a packing wear monitor.

9. (previously presented) The packing unit of claim 8, wherein:  
the compression unit comprises one or more coil springs located between first and second compression plates; and  
the packing wear monitor comprises a viewing port revealing the linear travel position of the second compression plate.

10. (previously presented) The packing unit of claim 3, wherein the packing material is captured on the steam tube and compressed by the compression unit when the packing unit is in the operative position and the detent mechanism is inactive.

11. (previously presented) The packing unit of claim 3, wherein the packing material is captured on the steam tube and compressed between an internal bushing and a plunger coupled to the second compression plate when the packing unit is in the operative position and the detent mechanism is inactive.

12. (previously presented) An integral and removable packing unit, comprising:  
a housing configured to be removably installed in an operative position in association with a sootblower steam tube and lance spindle with the steam tube passing through a cylindrical opening defined by the packing unit;

a plurality of concentric, equally-sized, sacrificial packing rings captured on the steam tube and configured to form a steam seal between the spindle and the steam tube when the packing unit is installed in an operative position and the packing material is loaded by a compression unit; and

wherein the housing, packing rings and compression unit comprise an integral unit constructed so as to be installed to and removed from the steam tube and spindle with the packing material held intact within the housing.

13. (previously presented) The packing unit of claim 12, wherein the compression unit is located within the housing.

14. (previously presented) The packing unit of claim 13, further comprising a detent mechanism for unloading the packing material to facilitate installing the packing unit on, and removing the packing unit from, the operative position.

15. (previously presented) The packing unit of claim 14, wherein the compression unit comprises one or more coil springs located between first and second compression plates.

16. (previously presented) The packing unit of claim 15, wherein the detent mechanism comprises one or more set screws that threadably engage at least one of the compression plates to compress the coil springs and thereby unload the packing material.

17. (previously presented) The packing unit of claim 16, further comprising a packing wear monitor including a viewing port revealing the linear travel position of the second compression plate.

18. (previously presented) A sootblower comprising:  
a steam tube;  
a lance tube telescopically received on the steam tube and having an associated lance spindle ;  
a housing for removably holding a sacrificial packing material configured to form a steam seal between the steam tube and the lance spindle when the packing unit is installed in an operative position and the packing material is loaded by applying compression to the packing material; and  
wherein the housing and packing material comprise an integral unit constructed so as to be installed to and removed from the stream tube and spindle with the packing material held intact within the housing.

19. (previously presented) The sootblower of claim 18, further comprising a compression unit for compressing the packing material to tighten the seal between steam tube and lance spindle when the packing unit is installed in the operative position.

20. (previously presented) The sootblower of claim 19, further comprising a detent mechanism for unloading the packing material to facilitate installing the packing unit on, and removing the packing unit from, the operative position.

21. (previously presented) The sootblower of claim 20, wherein the compression unit comprises one or more coil springs located between first and second compression plates.

22. (previously presented) The sootblower of claim 19, wherein the detent mechanism comprises one or more set screws that threadably engage at least one of the compression plates to compress the coil springs and thereby unload the packing material.

23. (previously presented) The sootblower of claim 18, wherein the packing material is sacrificial, further comprising a packing wear monitor.

24. (previously presented) The sootblower of claim 23, further comprising a packing wear monitor.

25-29 (canceled)